

HMLCD15

Description	Specification
LCD Panel	15.0"
LCD Type	Active Matrix TFT
Brightness	250 cd/m ² (typ)
Contrast	300:01:00
Viewing Angle	R/L : 60°/ 60°, U/D : 55°/ 60°
H-Frequency	31.5Khz ~ 63Khz
V-Frequency	56Hz ~ 75Hz
Resolution(max)	1024 X 768
Colors	Normal : 256K Colors
	Expansion : True Color
Compatibility	VGA 640x480 60~75Hz(Expand to XGA)
	SVGA 800x600 56~75Hz(Expand to XGA)
	XGA 1024x768 60~75Hz
	NTSC, PAL, SECAM(Auto detect)
Display Input	Analog R.G.B
	AV1: Composite Video, S-Video
Speaker	2 Way 2 Watts Speakers with Amplifier
Power Management	VESA DPMS
AC Adaptor	12V 3.33A
Power Consumption	25Watts(max.)
Plug & Play	DDC 1/2B
User Controls(OSD)	5 Languages, OSD Position
	Automatic Adjustment, Factory Preset
	H/V Position, Horizontal Size, Phase
	Brightness, Contrast, Colour R.G.B, Video Mode
Tilt	Up/Down : 30°/0°
Weight	4.2kg
Dimension (W x H x D)	Physical : 368mm(W) x 368mm(H) x 153mm(D)
	Without Stand : 368mm(W) x 355mm(H) x 46mm(D)
Environment	Operation Temperature : 0°C to 40°C
	Storage Temperature : -10°C to 50°C
	Humidity : 90% maximum

