

## HMLCD17

Description	Specification
LCD Panel	17.0"
LCD Type	Active Matrix TFT
Brightness	250 cd/m <sup>2</sup> (typ)
Contrast	350:01:00
Viewing Angle	R/L : 70°/ 70°, U/D : 60°/ 60°
H-Frequency	31.5Khz ~ 80Khz
V-Frequency	56Hz ~ 75Hz
Resolution(max)	1280 X 1024
Colors	Normal : 16.7M Colors
	Expansion : True Color
Compatibility	VGA 640x480 60~75Hz(Expand to SXGA )
	SVGA 800x600 56~75Hz(Expand to SXGA)
	XGA 1024x768 60~75Hz(Expand to SXGA)
	SXGA 1280 x 1024 60~75Hz
	NTSC, PAL, SECAM
Display Input	Analog R.G.B, AV1: Composite Video, S-Video
	AV2 : For TV Adaptor(only DiCON's)
Speaker	2 Way 2 Watts Speakers with Amplifier
Power Management	VESA DPMS
AC Adaptor	12V 5.0A
Power Consumption	60Watts(max.)
Plug & Play	DDC 1/2B
User Controls(OSD)	5 Languages, OSD Position
	Automatic Adjustment, Factory Preset
	H/V Position, Horizontal Size, Phase
	Brightness, Contrast, Colour R.G.B, Video Mode
	Audio Control, Video Control, Source Selection
Tilt	Up/Down : 30°/0°
Weight	8.2kg
Dimension (W x H x D)	Physical : 443mm (W) x 450mm (H) x 198mm (D)
	Without Stand : 443mm (W) x 439mm (H) x 60mm (D)
Environment	Operation Temperature : 0°C to 40°C
	Storage Temperature : -10°C to 50°C
	Humidity : 90% maximum

