

HMLCD19

Description	Specification
LCD Panel	19.0"
LCD Type	Active Matrix TFT
Brightness	250 cd/m ² (typ)
Contrast	500 : 1
Viewing Angle	R/L : 85°/ 85°, U/D : 85°/ 85°
H-Frequency	31.5Khz ~ 80Khz
V-Frequency	56Hz ~ 75Hz
Resolution(max)	1280 X 1024
Colors	Normal : 16.7M Colors
Video Compatibility	VGA 640x480 60~75Hz(Expand to SXGA)
	SVGA 800x600 56~75Hz(Expand to SXGA)
	XGA 1024x768 60~75Hz(Expand to SXGA)
	SXGA 1280 x 1024 60~75Hz
	PAL, NTSC, SECAM
Display Input	Analog R.G.B, AV1: Composite Video, S-Video
	AV2 : For TV Adaptor
Speaker	2 Way 2 Watts Speakers with Amplifier
Power Management	VESA DPMS
AC Adaptor	12V 5A
Power Consumption	60Watts(max.)
Plug & Play	DDC 1/2B
User Controls(OSD)	5 Languages, OSD Position, Automatic Adjustment, Factory Preset
	H/V Position, Horizontal Size, Phase, Brightness, Contrast, Color control
	Audio Control, Video Control, Source Selection
Wall Mount	VESA Standard 100mm
Tilt	Up/Down : 30°/0°
Weight	8.5kg
Dimension (W x H x D)	Physical : 443mm (W) x 450mm (H) x 198mm (D)
	Without Stand : 443mm (W) x 439mm (H) x 60mm (D)
Environment	Operation Temperature : 0°C to 40°C
	Storage Temperature : -10°C to 50°C
	Humidity : 90% maximum
Option	TV Adaptor

